



Make Your Event Dynamic / Z-1500II & Z-3000II Fog Machine

Antari proposes to you the Z-1500II and Z-3000II, the rigorous research and development resulting stability, durability, and reliability. When it comes to ultimate performance and precision control, the Z-1500II & Z-3000II will suit virtually any applications.

These fog machine provide significant advantages in a wide array of applications where volume of fog output is critical. Around 25% electricity is saved due to high efficient power control system allowing the fogger to operate at low-level temperature.

An electronic low fluid detector is also installed which automatically weakens pump power and stops pumping when running-out of fluid. They are fully controllable via Z-20 LCD control module supplied allowing the operator to set the volume control and timing precisely to the exact percentage from 1% to 100% output. DMX connection can be worked by either 3 or 5 pin connector.

These machines are Antari' s proud innovation; they are dedicated to most demanding professionals. Ideal for very large venues, outdoor event, movie

Z-1500II Fog Machine Specification

- » Power : AC100V/AC120V/AC230V/AC240V,50Hz-60Hz
- » Heater : 1,500 W
- » Output : 20,000 cu.ft / min
- » First Heat-up Time : 8.5 min
- » Tank Capacity : 6 liter
- » Fluid Consumption Rate : 9 min / liter (100% Output)
- » Remote Included : Z-20 Control Module
- » Optional Remotes : Z-30PRO Wireless Control Module
- » Weight : 14 Kg
- » Dimensions (mm) : L 688 W 285 H 188
- » DMX : On board
- » Liquid Used : Antari FLR / FLG

Z-3000II Fog Machine Specification

- » Power : AC230V/AC240V,50Hz-60Hz
- » Heater : 3,000 W
- » Output : 40,000 cu.ft / min
- » First Heat-up Time : 12 min
- » Tank Capacity : 6 liter
- » Fluid Consumption Rate : 5 min / liter (100% Output)
- » Remote Included : Z-20 Control Module
- » Optional Remotes : Z-30PRO Wireless Control Module
- » Weight : 19.9 Kg
- » Dimensions (mm) : L 735 W 310 H 192
- » DMX : On board
- » Liquid Used : Antari FLR / FLG

Z-20 Control Module


- » Cable Length : 2 M
- » Connector : 5 Pin XLR
- » Function : Timer with interval, duration and volume; set DMX address; continuous fogging; manual ON/OFF.



• Z-1500II Effect



• Z-3000II Effect



• Z-20 Control Module



• Z-30PRO Wireless Control Module (Optional)