

functional



arco 24 / arco 24T

arco12Sub



MODEL	<i>arco 24 / arco 24T</i>
Certification	IP54 (with IP-Kit), EN54 Pending
RMS (Average) Power Handling ⁽¹⁾	100 W
Peak Power Handling	400 W
Frequency Range (-10 dB) ⁽²⁾	65 Hz-22 kHz
Nominal Impedance	8 ohms
Transformer Taps 100 V	10, 20, 30 W
70 V	5, 10, 15 W
On-axis Sensitivity 1 W/ 1 m	89 dB SPL
Rated Maximum Peak SPL at 1 m ⁽³⁾	115 dB
HF Horn Coverage Angles (-6dB)	80° H x 70° V
Enclosure Material	High Impact ABS Paintable UV Resistant
Color/Finish	Black or White
Transducers/Replacement Parts	LF: 2 x 4G4/4G4 HF: TWT-24/TWT-24
Connectors	Spring Terminals
Dimensions (H x W x D)	34 x 15 x 15 cm 17.7 x 5.9 x 5.9 in
Weight	2.6 kg (5.7 lb)
Accessories	AX-4RM (Included) Wall Mount AXU-AC24 U Bracket AXA-AC Mounting Accessory

MODEL	<i>arco 12SUB</i>
Power Handling	170 W cont. program per coil
Frequency Range (-10 dB)	40 Hz - 200 Hz
Nominal Impedance	8 + 8 ohm (dual voice coil)
Sensitivity 1W/1m	106 dB SPL at corner junction ($\pi/2$ loading, 1/2 W each coil)
Rated Maximum Peak SPL	134 dB
Filter Network to Subwoofer	12 dB/oct low-pass, 200 Hz (per input)
Filter Network to Satellite Outputs	6 dB/oct high-pass (per output)
Transducer/Replacement Parts	122S/122S
Connectors	Spring terminals Left In, Right In Left Satellite Out Right Satellite Out
Enclosure Material	MDF
Color	Black
Dimensions (H x W x D)	36 x 59.2 x 28.5 cm 14.2 x 23.3 x 11.2 in
Weight	14 kg (30.8 lb)
Accessories	AXW-122S (Included) Wall Mount