

MSD Platinum (Touring/ Stage)

MSD Platinum 5 R UNP/24

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

Product data

• General Information

System Description

Cap-Base Operating Position UNIVERSAL [Any or Universal (U)]
Main Application Stage/Touring
Life To 50% Failures (Nom)

Reflector-E20.6

• Light Technical

Color Code 7100 lm Luminous Flux (Min) Luminous Flux 7950 lm (Nom) Chromaticity Coor-300 dinate X (Nom) Chromaticity Coor-300 dinate Y (Nom) 8000 K Correlated Color Temperature (Nom) Color Rendering Index (Nom)

· Operating and Electrical

Power (Rated) 189 W (Nom)

Warnings and Safety

 A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and · Controls and Dimming

Dimmable Yes

• Mechanical and Housing

Cap-Base Information

• Luminaire Design Requirements

Pinch Temperature 350 °C (Max)

• Product Data

Net Weight (Piece)

Full product code
Order product name
EAN/UPC - Product
Order code
Order code
Order product
Order code
Order code
Numerator - Quantity Per Pack
Numerator - Packs
Per outer box
Material Nr. (12NC)

87279008733400
MSD Platinum 5 R UNP/24
8727900783506
928190805308

MSD Platinum 5 R UNP/24
87279008733506
928190805308


0.120 kg

remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.



MSD Platinum (Touring/Stage)


Dimensional drawing



MSD Platinum 5 R

Product	D	Т	0	С
MSD Platinum 5 R UNP/24	51.4 mm	6.8 mm	1.0 mm	57.1 mm

Photometric data





Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.