

# HPL 93728 575 W 230 V

HPL | High-performance lamps



### **Product benefits**

– Optimum use of the generated light in the spotlight





## Product datasheet

#### Technical data


### **Electrical data**

Nominal wattage	575.00 W
Nominal voltage	230 V

### Photometrical data

Nominal luminous flux	14900 lm
Color temperature	3200 K

### **Dimensions & weight**











Diameter	19.0 mm
Length	104.0 mm
Length with base excl. base pins/connection	98.00 mm
Light center length (LCL)	60.3 mm
Illuminated field	9.5*11.5 mm² <sup>1)</sup>

<sup>1)</sup> Type of filament 6-C8

## Lifespan

Lifeenan	400 h
Lifespan	400 11

## Additional product data

Base (standard designation)	G9.5
-----------------------------	------

## **Capabilities**

Burning position	Any
------------------	-----

### Certificates & standards

EEI – Energy Label	В
--------------------	---

## Product datasheet

## **Country specific categorizations**

Order reference	93728 575W 230V
-----------------	-----------------

## Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300461816	OSRH93728	-	4736185	- -

### Product datasheet

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300461816	HPL 93728 575 W 230 V	Folding carton box 1	131 mm x 42 mm x 42 mm	0.23 dm <sup>3</sup>	68.50 g
4050300461823	HPL 93728 575 W 230 V	Shipping carton box 12	174 mm x - x 145 mm	3.36 dm <sup>3</sup>	947.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.