

HPL 93729 750 W 230 V

HPL | High-performance lamps



Product benefits

- Optimum use of the generated light in the spotlight



December 10, 2017, 13:05:57 HPL 93729 750 W 230 V

Technical data

Electrical data


Nominal wattage	750.00 W
Nominal voltage	230 V

Photometrical data

Color	temperature	
COLOI	temperature	

3200 K

Dimensions & weight









Diameter	19.0 mm	
Length	101.0 mm	
Length with base excl. base pins/connection	104.00 mm	
Light center length (LCL)	60.3 mm	
Illuminated field	7.5*11.5 mm ^{2 1)}	

1) Type of filament 6-C8

Lifespan

Lifespan	300 h	
Additional product data		
Base (standard designation)	2 pins	
Capabilities		
Burning position	Any	
Certificates & standards		
EEI – Energy Label	В	

Country specific categorizations

Order reference	93729 750W 230V
-----------------	-----------------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300654201	OSRH93729	-	-	-

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300654201	HPL 93729 750 W 230 V	Folding carton box 1	131 mm x 42 mm x 46 mm	0.25 dm ³	77.00 g
4050300654218	HPL 93729 750 W 230 V	Shipping carton box 12	174 mm x 148 mm x 145 mm	3.73 dm ³	953.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.