

Q-10



DESCRIPTION

This ultra-compact, low-profile subwoofer is ideal for small- and medium-sized installations. Low frequency clarity and reproduction make this an unbeatable system for delivering outstanding music reproduction. Perfect match for the Q Series tops.

KEY FEATURES

- Compact subwoofer system
- Birch plywood enclosure
- 1 DAS 10MG loudspeaker
- Frequency range 40 Hz - 200 Hz

APPLICATIONS

- A/V systems and corporate events
- Meeting rooms, classrooms, and exhibit areas
- Installations in bars and clubs

SPECIFICATIONS

Performance

Frequency Range (-10 dB)	40 Hz - 200 Hz
Nominal Impedance	8 Ohms
RMS Power Handling	250 W
Peak Power Handling	1000 W
On-axis Sensitivity 1W/1 m	94 dB SPL
Maximum Peak SPL at 1 m	121 dB
Recommended Amplifier	IA-404 IA-1004
Recommended Processor	DSP-226

Connectors

Audio Input Connector	1 x speakON NL4
Audio Output Connector	1 x speakON NL4

Enclosure

Enclosure Construction	Birch Plywood
Enclosure Geometry	Rectangular
Finish	ISO-flex Paint
Color	Black
Dimensions (H x W x D)	305 x 505 x 415 mm 12,0 x 19,9 x 16,3 in
Net Weight	16,0 kg (35,3 lb)

Components

LF Driver	10MG
-----------	------

Shipping

Shipping Weight	17,0 kg (37,5 lb)
-----------------	---------------------

ORDERING INFORMATION

Performance

Model	Description	P/N
-------	-------------	-----

System

Q-10	Passive Subwoofer	10434079
------	-------------------	----------

Replacement Parts

10MG	Cone Transducer	20208692
GM-10MG	Recone Kit	20208422

Accessories

SPK4-1	Electronic Accessories	20502000
SPK4-10	Electronic Accessories	20502001
SPK4-20	Electronic Accessories	20502002

DIMENSIONS

