



**PR 250T** is a 250 watts Tunable white LED Profile. It delivers a constant full power output with a color temperature tunable from 2700K to 5600K. It delivers a flat and crisp field of light tweaked in temperature and tint to guarantee the best color rendering on cameras. An optional high performance Fresnel lens with barn doors can replace the profile lens offering an even Fresnel wash from the same LED engine. With a high CRI of 97, this LED Profile is the perfect fit in studios and theatres.

**SOURCE** Light source: 500 watts COB LED 250 watts Warm White + 250 watts Cool white LED  
 Color temperature: 2700K-5600K  
 LED life expectancy: 50,000 Hrs  
 CRI: 97, R9 ≥ 90  
 TLCI: 98

**OPTICAL SYSTEM** Manual zoom  
 Zoom range: 18° to 38°  
 Optional Fresnel lens adapter 25°-50° (PMMA)  
 Optional Iris and Gobo holder

**KEY FEATURES** 5 Dimmer curves  
 Color mixing: Tunable white  
 Strobe  
 Video flicker free with selectable PWM  
 Intelligent temperature control  
 Silent operation

**CONTROL & PROGRAMMING** Control protocols: RDM, DMX, Rotary  
 Control channels: 2, 4, 5 CHs

**ELECTRICAL** Input voltage: AC100-240V/50-60Hz

**CONNECTIONS** DMX connections: 3 pin XLR In/Out male and female  
 Power connections: PowerCon In/Out

**PHYSICAL** Dimensions: 745 x 294 x 294mm  
 Net weight: 8.7 Kg (including lens)  
 Color: Black  
 IP rating: 20  
 Operation temperature: -5°C/45°C

## Dimensions

