





BOOMER 14Z is a 14 x 15 watts RGBW LED zoom LED PAR. It features a wide zoom range of 8° to 50° to cover most indoor wash applications. Ideal for entertainment and theatrical application with a low flickering source and a quiet operation.

SOURCE	Lighting source: 14 x 15 watts ,4 in RGBW LEDs Life expectancy: 50,000 Hrs.	Dimensions
	Life expectancy. 50,000 mis.	
	Beam angle: 8° to 50°	< 295.07mm →
SYSTEM		
DYNAMIC	Dimmer: 0-100% linear adjustment	
EFFECTS	Color mixing: RGBW	n11/00000/14
	4 dimmer curves	ROS!
	Variable strobe Built-in color and dynamic macros	
CONTROL &	Control protocols: DMX	< 356.42mm >
PROGRAMMING	Display: TFT display with 5 buttons operation	< 2/6.930mm → 259.69mm →
	Control channels: 2, 4, 8, 12, 14 CHs	
FI ECTRICAL	Input voltage: 100-240V/50-60Hz	
	Power consumption: 250 watts	
CONNECTIONS	DMX connections: 3 pin and 5 pin XLR In/Out male	
	and female Power connections: Powercon In/Out	
	Power connections. Powercon in/Out	Luminous Diagram
PHYSICAL	Dimensions: 295 x 226 x 356mm	
	Net weight: 6.3Kg	lastante entre lant state state lant
	Housing: Die-Cast Aluminum	
	Color: Black IP rating: 20	
	Operating temperature: -30°C/45°C	Disansating 5 3 4 5 6 16 Disansating 5 65 65 65 65 54 383
:		