









 $FLASH\ 55$ is a 1440 x 0.2 watts RGBW LED wash and strobe. It has a solid waterproof structure with an IP rating of 65. Each 12 LEDs can be controlled separately which brings out a dynamic wash and strobe effect. It can be floor seated or hanged on truss, perfectly fits any outdoor and indoor event and installation.

SOURCE Light source: 720x0.2 watts RGBW, LEDs

720x0.2 watts White LEDs

Lamp life expectancy: 50,000 Hrs.

OPTICAL Beam Angle: 110°

SYSTEM

EM

DYNAMIC Dimmer: Linear adjustment

EFFECTS Color mixing: RGBW 4 dimmer curves

Variable strobe

Individual zones control

Built-in color and dynamic macros

CONTROL & Control protocols: DMX, WDMX, Master-Slave

PROGRAMMING Display: 2.4" TFT display operation

Control channels: 4, 6, 10, 14, 16, 48, 50, 64CHs

ELECTRICAL Input voltage: 100-240V/50-60Hz

Power consumption: 280 watts

CONNECTIONS DMX connections: 3 pin XLR In/Out male and female

Power connections: IP Powercon In/Out

PHYSICAL Dimensions: 509x 326 x 226mm

Net weight: 12.9 Kg Housing: Aluminum

Color: Black IP rating: 65

Operating temperature: - 20°C/40°C





