







Dimensions



BLADE R8500 is a rotating laser bar with 8 beam laser outlets each equipped with a laser diode of 500 mW / 638 nm bright red and 7 amber LEDs of 3 watts with a beam angle of 7° for additional aerial effects. This special laser bar effect creates fans of laser beams along with a warm white beam effect controlled via DMX. It is ideal for stage, clubs, live gigs and show productions.

Power: 4 watts Wavelength: 638m Color: Red Laser safety: Class 3B Life expectancy: 2,000 Hrs. Modulation: TTL SCANNER Scan system: Stepper motor Scan angle: 180° LED SOURCE LED power: 7 x 3 watts amber LEDs Color temperature: 2200 K LED beam angle: 7° LED beam angle: 7° LED life expectancy: 50,000 Hrs. Pixel control Electronic strobe: 0-25 Hz Built- in dynamic macros CONTROL& PROGRAMMING Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT Titt: 180° ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power consumption: 68 watts Color: Black Prover connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IPrating: 20	LASER	Source: 8 x 500 mW diodes	Dimensions
Color: Red Laser safety: Class 3B Life expectancy: 2,000 Hrs. Modulation: TTL 1000 SCANNER Scan system: Stepper motor Scan angle: 180° LED SOURCE LED power: 7 x 3 watts amber LEDS Color temperature: 2200 K LED beam angle: 7° LED life expectancy: 50,000 Hrs. DYNAMIC EFFECTS Pixel control Electronic strobe: 0-25 Hz Built-in dynamic macros CONTROL & PROGRAMMING Control protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT Titt: 180° ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power consumption: 68 watts CONNECTIONS DMX connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20			
Life expectancy: 2,000 Hrs. Modulation: TTL Scan system: Stepper motor Scan angle: 180° LED SOURCE LED power: 7 x 3 watts amber LEDs Color temperature: 2200 K LED beam angle: 7° LED life expectancy: 50,000 Hrs. Pixel control Electronic strobe: 0-25 Hz Built-in dynamic macros CONTROL & Control protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT Tilt: 180° LECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power consumption: 68 Kg CONTROL & Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20			
Life expectating, 2,000 His. 1000 Modulation: TTL 1000 SCANNER Scan system: Stepper motor Scan angle: 180° LED SOURCE LED power: 7 x 3 watts amber LEDs Color temperature: 2200 K LED beam angle: 7° LED life expectancy: 50,000 Hrs. DYNAMIC EFFECTS Pixel control Electronic strobe: 0-25 Hz Built-in dynamic macros CONTROL & PROGRAMMING Control protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT Tilt: 180° ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight; 6.8 Kg Color: Black IP rating: 20			
SCANNER Scan system: Stepper motor Scan angle: 180° LED power: 7 x 3 watts amber LEDS Color temperature: 2200 K LED beam angle: 7° LED life expectancy: 50,000 Hrs. DYNAMIC Pixel control EFFECTS Pixel control CONTROL & Control protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT Tilt: 180° ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20			
Scan angle: 180°LED SOURCELED power: 7 x 3 watts amber LEDs Color temperature: 2200 K LED beam angle: 7° LED life expectancy: 50,000 Hrs.DYNAMICPixel control Electronic strobe: 0-25 Hz Built-in dynamic macrosCONTROL & PROGRAMMINGControl protocols: DMX, Auto, Sound, Master-slave Display. LED display with 4 control buttons DMX channels: 7, 22 CHsMOVEMENTTilt: 180°ELECTRICAL Power consumption: 68 wattsCONNECTIONSDMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/OutPHYSICAL IDimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black I Prating: 20		Modulation: IIL	1000
Scan angle: 180°LED SOURCELED power: 7 x 3 watts amber LEDs Color temperature: 2200 K LED beam angle: 7° LED life expectancy: 50,000 Hrs.DYNAMICPixel control Electronic strobe: 0-25 Hz Built-in dynamic macrosCONTROL & PROGRAMMINGControl protocols: DMX, Auto, Sound, Master-slave Display. LED display with 4 control buttons DMX channels: 7, 22 CHsMOVEMENTTilt: 180°ELECTRICAL Power consumption: 68 wattsCONNECTIONSDMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/OutPHYSICAL IDimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black I Prating: 20	SCANNER	Scan system: Stepper motor	
Color temperature: 2200 K LED beam angle: 7° LED life expectancy: 50,000 Hrs. Pixel control Electronic strobe: 0-25 Hz Built-in dynamic macros CONTROL & PROGRAMMING DYNAMIC Control protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black LP and the dist of the strong in the strong			
Color temperature: 2200 K LED beam angle: 7° LED life expectancy: 50,000 Hrs. Pixel control Electronic strobe: 0-25 Hz Built-in dynamic macros CONTROL & PROGRAMMING DYNAMIC Control protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black LP and the dist of the strong in the strong			
LED beam angle: 7° LED life expectancy: 50,000 Hrs.DYNAMIC EFFECTSPixel control Electronic strobe: 0-25 Hz Built-in dynamic macrosCONTROL & PROGRAMMINGControl protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHsMOVEMENTTilt: 180°ELECTRICAL Power consumption: 68 wattsCONNECTIONSDMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/OutPHYSICALDimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IPrating: 20	LED SOURCE		
LED life expectancy: 50,000 Hrs.DYNAMIC EFFECTSPixel control Electronic strobe: 0-25 Hz Built-in dynamic macrosCONTROL & PROGRAMMINGControl protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHsMOVEMENTTilt: 180°ELECTRICAL Power consumption: 68 wattsCONNECTIONS PHYSICALDMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/OutPHYSICAL PHYSICAL Pictor: Black (Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black (Prating: 20)			
DYNAMIC EFFECTS Pixel control Electronic strobe: 0-25 Hz Built-in dynamic macros CONTROL & PROGRAMMING Control protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT Tilt: 180° ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20			
EFFECTS Electronic strobe: 0-25 Hz Built-in dynamic macros CONTROL & PROGRAMMING Control protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT Tilt: 180° ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20			
EFFECTSElectronic strobe: 0-25 Hz Built-in dynamic macrosCONTROL & PROGRAMMINGControl protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHsMOVEMENTTilt: 180°ELECTRICALInput voltage: AC100-240V/50-60Hz Power consumption: 68 wattsCONNECTIONSDMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/OutPHYSICALDimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20			173
CONTROL & PROGRAMMINGControl protocols: DMX, Auto, Sound, Master-slave Display: LED display with 4 control buttons DMX channels: 7, 22 CHsMOVEMENTTilt: 180°ELECTRICALInput voltage: AC100-240V/50-60Hz Power consumption: 68 wattsCONNECTIONSDMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/OutPHYSICALDimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20	EFFECTS		
PROGRAMMING Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT Tilt: 180° ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20		Built-in dynamic macros	
PROGRAMMING Display: LED display with 4 control buttons DMX channels: 7, 22 CHs MOVEMENT Tilt: 180° ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20	CONTROL &	Control protocols: DMX Auto Sound Master-slave	
DMX channels: 7, 22 CHs MOVEMENT Tilt: 180° ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20			
ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20			
ELECTRICAL Input voltage: AC100-240V/50-60Hz Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20			
Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20	MOVEMENT	Tilt: 180°	
Power consumption: 68 watts CONNECTIONS DMX connections: 3 pin XLR In/Out male and female Power connections: PowerCon In/Out PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20		Ipput voltage: AC100-240\//50-60Hz	
CONNECTIONS DMX connections: 3 pin XLR In/Out male and female PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20 Dimensions: 20	LLCINCAL		
Power connections: PowerCon In/Out Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20			
PHYSICAL Dimensions: 1000 x 84 x 173mm Net weight: 6.8 Kg Color: Black IP rating: 20	CONNECTIONS		
Net weight: 6.8 Kg Color: Black IP rating: 20		Power connections: PowerCon In/Out	
Net weight: 6.8 Kg Color: Black IP rating: 20		Dimensions: 1000 x 84 x 173mm	
Color: Black IP rating: 20	PRIJCAL		
		IP rating: 20	
	i	Operating temperature: 10°C/40°C	