

ES-26



KEY FEATURES

- Twin 6" loudspeakers
- M-34 compression driver
- Vertical or horizontal positioning
- Threaded fixing points for wall mounts

DESCRIPTION

The ES-26 employs twin 6P (2" VC) woofers for low-mid frequency reproduction and an M-34 compression driver, which provides brilliant highs.

The symmetrical horn (80°x 80°) offers precise coverage and control allowing the cabinets to be installed in the horizontal and vertical position.

The ES-26 is a compact system designed using top grade birch plywood and protected with an impact resistant ISO-flex paint. The front elements of the cabinet are protected using a solid metal grill assisted by an acoustically transparent fabric.

APPLICATIONS

- Nightclubs
- VIP Rooms
- Bar & Lounges
- Live Music Venues

SPECIFICATIONS

Performance

Frequency Range (-10 dB)	60 Hz – 20 kHz
Horizontal Coverage (-6 dB)	80°
Vertical Coverage (-6 dB)	80°
Nominal Impedance	16 ohms
RMS Power Handling	400 W
Peak Power Handling	1600 W
On-axis Sensitivity 1W/1 m	93 dB SPL
Maximum Peak SPL at 1 m	125 dB
Recommended Amplifier	DX-80
Recommended Processor	IO-48

Connectors

Audio Input Connector	1 x speakON NL4
Audio Output Connector	1 x speakON NL4

Enclosure

Enclosure Construction	Birch Plywood
Enclosure Geometry	Trapezoidal
Rigging	M10 Rigging Points
Finish	ISO-flex Paint
Color	Black
Dimensions (H x W x D)	195x 550x 260mm 7,7 x 21,7 x 10,2 in
Net Weight	11kg (24,3 lb)

Components

LF Driver	6P
HF Driver	M-34
Horn/Waveguide	BC-88

ORDERING INFORMATION

Model	Description	P/N
-------	-------------	-----

System

ES-26	2-way Passive Point Source	10433175
--------------	----------------------------	----------

Replacement Parts

6P	Transducer	20208730
BC-88	Horn	30003945
F-AR526	Filter	30005457
GM-M34	Diaphragm	20205060
M-34	Compresion Driver	10207080

Shipping

Carton Dimensions (H x W x D)	266 x 638x 330 mm 10,5 x 25,1 x 13 in
Shipping Weight	16,1 kg (35,5 lb)

Accessories

ANL-2	Installation & Stacking Acc.	10101020
AX-SPG1	Installation & Stacking Acc.	10105050
AX-SPG2	Installation & Stacking Acc.	10105060
AXC-AT	Installation & Stacking Acc.	10104310
AXR-AR5	Installation & Stacking Acc.	10104870
AXC-ZT	Installation & Stacking Acc.	10104320
AXU-AR526	Installation & Stacking Acc.	10104520
AXW-1	Installation & Stacking Acc.	10104140

DIMENSIONS

