# artec 300 series



# **ARTEC-315.96**



#### **DESCRIPTION**

The ARTEC-315.96 is a compact 2-way full-range loudspeaker system comprised of one 15" low frequency transducer and one M-34 compression driver with titanium diaphragm. The rotatable waveguide provides 90° x 60° coverage and allows the systems to be installed in either the vertical or horizontal position maintaining the needed dispersion characteristics.

The Artec-300 cabinets are constructed from Baltic Birch plywood and finished with a durable ISO-flex paint. The trapezoidal enclosure design helps eliminate standing wave coloration and at the same time, permits close-packed horizontal or vertical arrays.

#### **KEY FEATURES**

- ·1 x 15MI low frequency loudspeaker, 2.5" VCD
- $\cdot$ 1 x M-34 compression driver
- · Rotatable 90° x 60° horn
- · Vertical or horizontal positioning
- · Optional AXU-AR315 U-Bracket
- M10 rigging points

#### **APPLICATIONS**

- $\cdot$  A/V systems and corporate events
- · Meeting rooms, classrooms, and exhibit areas
- · Installations in bars and clubs

The cabinet is fitted with M10 threaded suspension points. Four VESA75/VESA100 standard threaded mounting points on the rear of the cabinet provide a secure fixing point for DAS mounting brackets.

### **SPECIFICATIONS**

Performance	
Frequency Range (-10 dB)	47 Hz - 20 kHz
Horizontal Coverage (-6 dB)	90°
Vertical Coverage	60°
Nominal Impedance	8 ohms
RMS Power Handling	350 W
Peak Power Handling	1400 W
On-axis Sensitivity IW/I m	96 dB SPL
Maximum Peak SPL at 1 m	127 dB
Recommended Amplifier	PA-1500
Recommended Processor	DSP-226
Compostors	
Connectors	Covered Barrier Strip Terminals
Audio Input Connector	Covered Barrier Strip Terminals
Audio Output Connector	Covered Barrier Strip Terminals
Englague	
Enclosure	
Enclosure Construction	Birch Plywood
Enclosure Geometry	Trapezoidal
Rigging	M10 Rigging Points
Finish	ISO-flex Paint
Color	Black



Depth	380 mm (15,0 in)	
Dimensions ( H x W x D )	715 x 445 x 380 mm 28,2 x 17,5 x 15,0 in	
Net Weight	22,5 kg ( 49,6 lb )	
Components		
LF Driver	15MI	
HF Driver	M-34	
Horn/Waveguide	BC-916	
Shipping		
Carton Dimensions ( H x W x D )	810 x 440 x 510 mm 31,9 x 17,3 x 20,1 in	
Shipping Weight	24,5 kg ( 54,0 lb )	

# **ORDERING INFORMATION**

Performance		
Model	Description	P/N
	,	
System		
ARTEC-315.96		10423828
Replacement Parts		
15MI	Cone Transducer	10214290
BC-916	Horn	30006590
F-AR315	Filter	30006593
GM-15MI	Recone Kit	20208270
GM-M34	Diaphragm	20205060
LAMP-F-21	Lamp	30000535
M-34	Compression Driver	10207080
Accessories		
ANL-2	Rigging Accessories	10101020
AX-SPG1	Installation & Stacking Acc.	10105050
AXC-AT	Installation & Stacking Acc.	10104310
AXR-AR5	Installation & Stacking Acc.	10104870
AXU-AR315	Installation & Stacking Acc.	10105110

## **DIMENSIONS**









