



## Point 8

The Point 8 is the smallest member of the Point Series family, yet it packs a lot of punch for its size. It will be right at home with speech systems or moderate level playback systems, but is still powerful enough to take on jazz bands and other lighter live music.

The Point 8 is available in passive and active(Bi-amped) versions. At its heart lies a single Adamson 8" ND8-LM 16Ω Kevlar Neodymium Driver, and 1" Exit HF driver mounted on an Adamson fiberglass waveguide. The point 8's rotatable 90° x 60° waveguide offers a defined coverage pattern, and its hexagonal shape allows use as a monitor without any additional adjustments.

### Specifications

Frequency Range (+/- 3dB)	65 Hz - 20 kHz
Nominal Directivity (-6dB) H x V	90° x 60° Rotatable
Maximum Peak SPL**	130.6 dB
Components LF	ND8-LM 8" Kevlar Neodymium Driver
Components HF	B&C DE500 1.7" Diaphragm / 1" Exit Compression Driver
Nominal Impedance Passive	8 Ω
Power Handling (AES / Peak) Passive	300 / 1200 W
Rigging	4x SLR™ Socket, Omni Mount 30 Series, Built-in Polemount Socket
Connection	2x Speakon™ NL4 (Barrier Strip Optional)
Height Front (mm/in)	451 / 17.75
Width (mm/in)	251 / 9.88
Depth (mm/in)	251 / 9.88
Weight (kg / lbs)	12.5 / 27.6
Processing	Lake, IPD, XTA

\*\*12 dB crest factor pink noise at 1m, free field, using specified processing and amplification

