

# Power Rack Xtreme CPR32-C2-F7-CB

1x CEE32A In / Daisy chain – 7 x Schuko Typ F Out.

Power Rack Xtreme is a powerful and highly reliable distribution solution for installation in the 19" Rack. It is ideally suited for amplifier rack wiring application.



## Features & Benefits

- High quality electrical and electronical component from the renowned brands
- Circuit protection with residual current device (RCCB) and miniature circuit breakers (MCB)
- High quality assembly in EU
- Attractive price / value ratio

## Markets & Applications

- Markets: Professional audio esp. amp rack wiring / lighting / video wall
- Mobile applications: Festivals, live events. Control panels / rooms.
- Semi-permanent applications: Theaters, studios, fairs. Control panels /rooms.

## Ordering information

Article name	Details	Order code
CPR32-C2-F7-CB	FRONT: IN 1x CEE32A; Daisy chain 1x CEE32A; OUT 1x Schuko Type F; Circuit protection: 1x RCCB, 3x MCB. BACK: OUT 6x Schuko Type F	1028798

## Technical Information

Product	
<b>Input device</b>	1x CEE32A 5P red (front)
<b>Daisy chain</b>	1x CEE32A 5P red (daisy chain) front
<b>Output device</b>	7x Schuko socket with lid

Electrical	
<b>Circuit protection</b>	1x RCCB 40/0,03A 3x MCB 1pol C16
<b>Phase control indicator</b>	L1, L2, L3, green
<b>Rated voltage</b>	415V/AC, 50Hz
<b>Rated Current</b>	CEE socket: 415V Link Schuko socket 230V 16A

Mechanical	
<b>Weight</b>	3,8kg
<b>Type of construction</b>	19" Housing 2 HE, 1,5TE
<b>Dimensions</b>	483 x 88 x 104 mm (without fittings)

Material	
<b>Housing</b>	Metal
<b>Color</b>	black

## Environmental

<b>Protection class</b>	IP20
<b>Temperature range</b>	-5 to +40°C