



FR 40F is designed for short distance wash. It is a super compact, easy for setup LED Fresnel powered by 40 watts RGBW COB LED. Featuring 25° to 80° zoom and rotary control of dimmer. It delivers a smooth, soft and flat field of light. A barn door is included to shape the light.

SOURCE : Light source: 40 watts RGBW COB LED
LED life expectancy: 50,000 Hrs

OPTICAL SYSTEM : Manual zoom
Zoom range: 25° to 80°
Light output: 5,000 Lux @ 2m @ 25°

PHOTOMETRICS : CRI (Color Rendering Index) : >95; R9>90
CQS (Color Quality Scale): >96
TM-30 Rf (IES TM-30-15 Fidelity Index): >92
TM-30 Rg (IES TM-30-15 Gamut Index): >98
TLCI (Television Lighting Consistency Index): >98

KEY FEATURES : 5 Dimmer curves
Strobe
Video flicker free
PMMA polymethyl methacrylate lens
Barn doors included


CONTROL & PROGRAMMING : Control protocols: Rotary, DMX, RDM
Control channels: ARC.1(3CH), AR1.D(4CH), ARC.2(4CH), AR2.D(5CH), AR2.S(6CH), HSV(3CH), STAG(11CH)

ELECTRICAL : Input voltage: AC100-240V/50-60Hz
DMX Connections: 5 pin XLR In/Out male and female


CONNECTIONS : Power connections: PowerCon In

PHYSICAL : Dimensions: 230 x 156 x 279mm
Net weight: 2.2 Kg, Color: Black
Housing: Aluminum, IP rating: 20
Operating temperature: -5°C/45°C

Dimensions



230



279

156

Luminous Diagram

